

Models	2.5	3.5
Kilowatts	2	2.6
Max.RPM at Full Throttle	4500 - 5500	5000 - 6000
Cylinders	1	1
Smart Craft Compatible	N/A	N/A
Displacement	85 cc	85 cc
Starting	Manual	Manual
Gear Ratio	2.15:1	2.15:1
Gear Shift	F-N	F-N
Steering Midsection	Tiller	Tiller
Alternator System	N/A	N/A
Fuel System	CARB	CARB
Trim Positions	4	4
Fuel Tank	0.95 litre INT	0.95 litre INT
Fuel Requirements	UL95R	UL95R
Weight	17 kg	17 kg
Available Boat Transom Heights	S	S - L
Counter Rotation	N/A	N/A

	4	5 / Sailpower	6
Kilowatts	2.9	3.7	4.4
Max.RPM at Full Throttle	4500 - 5500	4500 - 5500	5000 - 6000
Cylinders	1	1	1
Smart Craft Compatible	N/A	N/A	N/A
Displacement	123 cc	123 cc	123 cc
Starting	Manual	Manual	Manual
Gear Ratio	2.15:1	2.15:1	2.15:1
Gear Shift	F-N-R	F-N-R	F-N-R
Steering Midsection	Tiller-RO	Tiller-RO	Tiller-RO
Alternator System	OPT	4 amp (50 W) ML 4 amp (50 W)	OPT
Fuel System	CARB	CARB	CARB
Trim Positions	6 & SWD	6 & SWD	6 & SWD
Fuel Tank	1.1 L INT - RO	1.1 L INT - RO	1.1 L INT - RO
Fuel Requirements	UL95R	UL95R	UL95R
Weight	25 kg	25 kg	25 kg
Available Boat Transom Heights	S - L	S - L - XL S - L	S - L
Counter Rotation	N/A	N/A	N/A

GEAR SHIFT **DTS:** Digital Throttle and Shift • **F-N-R:** Mechanical Forward Neutral Reverse • **F-N:** Forward Neutral

STEERING MIDSECTION **AMS:** Advanced Mid Section • **CMS:** Conventional Mid Section
EHPS: Electric Hydraulic Power Steering
BTO: Big Tiller Optional • **RO:** Remote optional

ALTERNATOR SYSTEM **ESM:** On Electric Start Models only • **OPT:** Optional
OPT: Optional 4 amp (50 W) lighting, 2 amp (25 W) charging
ML: ML Models only

FUEL SYSTEM **EFI:** Electronic Fuel Injection • **Sci:** Super Charge Injection
DFI: Direct Fuel Injection • **CARB:** through carburetor


TRIM SYSTEM **EHPT:** Electric Hydraulic Power Trim and Tilt • **EHT:** Electric Hydraulic Tilt (no Trim) • **GAT:** Gas assist trim • **GMTT:** Manual Trim and Tilt
SWD: Shallow Water drive

FUEL TANK **INT:** Integrated fuel tank • **RO:** remote optional


AVAILABLE BOAT

TRANSOM HEIGHTS 381 mm(S) - 508 mm(L) - 635 mm(XL) - 762 mm(XXL)


COUNTER ROTATION 635 mm(CXL) - 762 mm(CXXL)




2.5hp & 3.5hp



2.5hp short shaft only



4hp, 5hp & 6hp



4hp, 5hp & 6hp