

Outboard Specifications



4-STROKE Models	Kilowatts ⁽¹⁾	Max. RPM at full throttle	Cylinders / Displacement	Starting	Gear ratio	Alternator system ⁽²⁾	Weight ⁽³⁾
400 Verado	294	6400 - 7000	6 (in-line) / 2598 cc	SmartStart electric	1.75 : 1	70 amp (882 watt)	303 kg
350 Verado	261	5800 - 6400	6 (in-line) / 2598 cc	SmartStart electric	1.75 : 1	70 amp (882 watt)	303 kg
NEW 300 - 250 Verado	224 - 186	5200 - 6000	V8 / 4600 cc	SmartStart electric	1.85 : 1	70 amp (882 watt)	272 kg
NEW 225 - 200 - 175	168 - 149 - 130	225: 5200 - 6000 200 - 175: 5000 - 5800	V6 / 3400 cc	SmartStart electric	1.85 : 1	85 Amp (1071 watt)	216 kg
150EFI	110.3	5000 - 5800	4 (in-line) / 3000 cc	Electric (turn-key)	1.92 : 1	60 amp (756 watt)	206 kg
90 Marathon	66.2	5000	4 (in-line) / 3000 cc	Electric (turn-key)	1.92 : 1	60 amp (756 watt)	206 kg
115 EFI - 90 EFI - 75EFI	84.6 - 66.2 - 55.2	115: 5000 - 6000 90-75: 4500 - 5500	4 (in-line) / 2100 cc	SmartStart electric	2.07 : 1 CT: 2.38 : 1	35 amp (441 watt)	115: 165 kg 90 - 75 : 163 kg
60 Marathon 50 Marathon	44.12 - 36.77	5000	4 (in-line) / 2100 cc	SmartStart electric	2.38 : 1	35 amp (441 watt)	165 kg
60EFI + CT 50 EFI	44.1 - 36.8	5500 - 6000	4 (in-line) / 995 cc	Electric (turn-key)	1.83 : 1 CT: 2.33 : 1	18 amp (226 watt)	112 kg CT: 118 kg
40 EFI	29.4	5500 - 6000	3 (in-line) / 747 cc	Electric (turn-key)	2.00 : 1	18 amp (226 watt)	98 kg
30 Marathon	22.06	4000	4 (in-line) / 1000 cc	Electric (turn-key)	2.33 : 1	18 amp (226 watt)	118 kg
30 ⁽³⁾ - 25 EFI ⁽³⁾	22.1 - 18.4	30: 5250 - 6250 25: 5000 - 6000	3 (in-line) / 526 cc	Manual or electric (turn-key)	1.92 : 1	15 amp (186 watt)	30: 78 kg 25: 71 kg
20 ⁽³⁾ - 15 EFI ⁽³⁾	14.7 - 11	5700 - 6200	2 (in-line) / 333 cc	Manual or electric	2.15 : 1	12 amp (138 watt)	45 kg
9.9 ⁽³⁾ - 8 ⁽³⁾	7.28 - 5.88	5000 - 6000	2 (in-line) / 208 cc	Manual or electric	2.08 : 1	6 amp (76 watt) on electric start models	38 kg
6 ⁽⁵⁾ - 5 ⁽⁵⁾ - 4 ⁽⁵⁾ + 5 SailMate ⁽⁵⁾	4.41 - 3.68 - 2.94	6: 5000 - 6000 5 - 4: 4500 - 5500	1 / 123 cc	Manual	2.15 : 1	Optional 4 amp (50 watt) lighting, 2 amp (25 watt) charging 5 SAILMATE: Standard with rectifier	25 kg
3.5 ⁽⁶⁾ - 2.5 ⁽⁶⁾	2.57 - 1.84	3.5: 5000 - 6000 2.5: 4500 - 5500	1 / 85 cc	Manual	2.15 : 1	n/a	17 kg
2-STROKE Models	Kilowatts ⁽¹⁾	Max. RPM at Full Throttle	Cylinders/ Displacement	Starting	Gear Ratio	Alternator System ⁽²⁾	Weight ⁽³⁾
50 - 40	36.8 - 29.4	5150 - 5850	3 / 697 cc	Manual or Electric	1.85:1	11 amp (130 watt)	75 kg
30 - 25	22.1 - 18.4	30: 4800 - 5500 25: 5000 - 5800	2 / 429 cc	Manual or Electric	1.92:1	6 amp (80 watt)	51 kg
15	11	5200 - 5800	2 / 249 cc	Manual	1.85:1	6 amp (76 watt)	42 kg
5 ⁽⁴⁾	3.68	4000 - 5000	1 / 102 cc	Manual	2.15:1	Optional 4 amp (50 watt) lighting	20 kg
3.3 - 2.5	2.4 - 1.8	3.3: 4500 - 5500 2.5: 4200 - 5200	1 / 74.6 cc	Manual	3.3: 2.15:1 2.5: 1.85:1	N/A	13 kg

(1) Measured at propshaft in accordance with ICOMIA 28. (2) Requires rectifier to complete installation manual versions.

(3) Dry weight specification is for lightest model and excludes engine oil, rigging hardware and propeller.